



Industrial expertise globally

for **80** years and  
**50** years in Türkiye

ARMOLINE BROŞÜR - TR - 09/2025/500/01

Approximately



**900** employees



from **23** countries



**7** production  
facilities in **6**  
countries

Global

**expert**

in lightweight roofing  
materials



**Onduline**

Lightweight Roofing and Waterproofing Materials

Değirmen St. Nida Kule  
No: 18 Kat: 8 34742  
Kozyatağı/Kadıköy/İstanbul  
Phone: 0216 384 16 00  
[onduline.com.tr](http://onduline.com.tr)

[pazarlama@onduline.com.tr](mailto:pazarlama@onduline.com.tr)

[f](#) [X](#) [o](#) YouTube /ondulineavrasya

444 8 663



**ARMOLINE**®  
by Onduline®

Enhanced  
Protection  
Against Hail  
Impacts



**ONDULINE ARMOLINE®** roofing sheets are composed of a combination of bitumen-impregnated organic fibres and a special kind of resin. Thanks to the content integrated with a special method into the sheet, the resistance of ARMOLINE® sheets to harsh weather conditions such as hail has been increased.

With its flexible structure, it does not crack, rust, or mold and is resistant to UV rays. It is a practical and user-friendly solution with its lightness and easy-to-apply structure.

### BENEFITS

- ▶ ONDULINE ARMOLINE® sheets offer a 10-year color guarantee and a 15-year water resistance warranty.
- ▶ Your roof color is preserved for many years with ARMOLINE® sheets, manufactured with ONDULINE Duratech's durable color technology.
- ▶ It has high hail resistance. Successfully tested at the Hail and Impact Resistance Laboratory of Adnan Menderes University's Department of Civil Engineering, the product performed well in tests and has been shown to resist hailstones of 20 mm diameter when used together with Villapor.
- ▶ When used with Villapor system product, it provides additional sound and thermal insulation for the roof while also enhancing overall durability.
- ▶ Its unique design features bands that offer a distinctive and aesthetic appearance.
- ▶ With the "1 groove 1 pitch" design, sheets are quick and easy to install, while groove ranges offer convenient mobility during installation.
- ▶ It is designed to perform reliably in various weather conditions.
- ▶ ONDULINE ARMOLINE® sheets do not rot and are resistant to biological factors such as mold and fungi.
- ▶ Salts, acids, and alkalies in various forms do not lead to a corruption in the performance of sheets.

### FEATURES

SHEET LENGTH	2.00 m
SHEET WIDTH	0.89 m
GROOVE PITCH	9.7 cm
SHEET AREA	1.78 m <sup>2</sup>
NET COATING AREA	1.50 m <sup>2</sup>
THICKNESS	3.3 mm
WEIGHT	6.05 kg/sheet
m <sup>2</sup> WEIGHT	3.4 kg/m <sup>2</sup>
GROOVE HEIGHT	38 mm
NUMBER GROOVES/FLATS	5 grooves 4 flats
FIRE REACTION	E
EXTERNAL FIRE REACTION	F <sub>ROOF</sub>
NUMBER OF PALLETS (NET)	350 units/pallets

### COLORS



### ACCESSORIES



Please visit [onduline.com.tr](http://onduline.com.tr) for color alternatives and product codes.